Construction Products Regulation

Declaration of Performance

1. Door Type EXS40R Residential Garage Door

2. Serial no Unique drawing reference

3. Operation Power operated door

4. Intended use External door for vehicle access

5. Manufacturer OSA Door Parts Ltd

Ashville Industrial Estate

Runcorn Cheshire UK WA7 3EZ

6. Assessment Level 3

7. Harmonised Standard BS EN 13241-1:2003 + A1:2011

0402-CPR-471401

SP Technical Research Institute of Sweden performed Initial Type Tests under system 3 and issued test report SP ref: PX28459K

8. Declared Performance

Essential Characteristic	Declared performance	Harmonised Standard
Watertightness	Class 3	
Dangerous substances	None	EN 13241-1:2003 + A1:2011
Resistance to wind load	5	
Thermal resistance	0.9 W/m ² .K	
Air Permeability	Class 3	
Safe opening - for vertically opening doors	Pass	
Definition of geometry of glass components	Pass	
Mechanical resistance and stability	Pass	
Operating forces	Pass	
Durability of water	Pass	
tightness, thermal resistance and air permeability		

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 5.

Signed for and on behalf of the manufacturer by:

W.Hammond Director October 2015

